



#### **BF25 - 15 in.**

Engine Type: 4-Stroke SOHC 3 Cylinder - 2 Valves/ Cyl.

Propshaft Horsepower: 25 HP @ 5,500 RPM

Weight: 155 lb. (70.5 kg)

Bore X Stroke: 2.4 in. x 2.5 in. (61 mm x 63 mm)



#### **BF25 - 15 in.**

Engine Type: 4-Stroke SOHC 3 Cylinder - 2 Valves/ Cyl.

Propshaft Horsepower: 25 HP @ 5,500 RPM

Weight: 155 lb. (70.5 kg)

Bore X Stroke: 2.4 in. x 2.5 in. (61 mm x 63 mm)



#### **BF30 - 15 in.**

Engine Type: 4-Stroke SOHC 3 Cylinder - 2 Valves/ Cyl.

Propshaft Horsepower: 30 HP @ 6,000 RPM

Weight: 155 lb. (70.5 kg)

Bore X Stroke: 2.4 in. x 2.5 in. (61 mm x 63 mm)



#### **BF30 - 20 in.**

Engine Type: 4-Stroke SOHC 3 Cylinder - 2 Valves/ Cyl.

Propshaft Horsepower: 30 HP @ 6,000 RPM

Weight: 160 lb. (72.5 kg)

Bore X Stroke: 2.4 in. x 2.5 in. (61 mm x 63 mm)



#### **BF40 - 20 in.**

Engine Type: 4-Stroke SOHC, 3 Cylinder, 2 Valves/Cyl.

Propshaft Horsepower: 40 HP @ 5,500 RPM

Weight: 214 lb. (97 kg)

Bore X Stroke: 2.8 in. x 2.8 in. (70 mm x 70 mm)





#### **BF50 - 20 in.**

Engine Type: 4-Stroke SOHC, 3 Cylinder, 2 Valves/Cyl.

Propshaft Horsepower: 50 HP @ 6,000 RPM

Weight: 214 lb. (97 kg)

Bore X Stroke: 2.8 in. x 2.8 in. (70 mm x 70 mm)



#### **BF50 - 25 in.**

Engine Type: 4-Stroke SOHC, 3 Cylinder, 2 Valves/Cyl.

Propshaft Horsepower: 50 HP @ 6,000 RPM

Weight: 223 lb. (101 kg)

Bore X Stroke: 2.8 in. x 2.8 in. (70 mm x 70 mm)



#### **BF60 - 20 in.**

Engine Type: 4-Stroke SOHC 3 Cylinder/12 Valves

Propshaft Horsepower: 60 HP @ 5,500 RPM

Weight: 239 lb. (108 kg)

Bore X Stroke: 2.9 in. x 3.1 in. (73 mm x 79.5 mm)



#### **BF60 - 25 in.**

Engine Type: 4-Stroke SOHC 3 Cylinder/12 Valves

Propshaft Horsepower: 60 HP @ 5,500 RPM

Weight: 251 lb. (114 kg)

Bore X Stroke: 2.9 in. x 3.1 in. (73 mm x 79.5 mm)



#### **BF75 - 20 in.**

Engine Type: 4-Stroke SOHC 4 Cylinder/16 Valves

Propshaft Horsepower: 75 HP @ 5,500 RPM

Weight: 359 lb. (163 kg)

Bore X Stroke: 3.0 in. x 3.5 in. (73 mm x 89.4 mm)





#### **BF90 - 20 in.**

Engine Type: 4-Stroke SOHC 4 Cylinder/16 Valves

Propshaft Horsepower: 90 HP @ 5,800 RPM

Weight: 359 lb. (163 kg)

Bore X Stroke: 3.0 in. x 3.5 in. (73 mm x 89.4 mm)



#### **BF90 - 25 in.**

Engine Type: 4-Stroke SOHC 4 Cylinder/16 Valves

Propshaft Horsepower: 90 HP @ 5,800 RPM

Weight: 365 lb. (166 kg)

Bore X Stroke: 3.0 in. x 3.5 in. (73 mm x 89.4 mm)



#### **BF60 - 20 in.**

Engine Type: 4-Stroke SOHC 3 Cylinder/12 Valves

Propshaft Horsepower: 60 HP @ 5,500 RPM

Weight: 239 lb. (108 kg)

Bore X Stroke: 2.9 in. x 3.1 in. (73 mm x 79.5 mm)



#### **BF100 - 20 in.**

Engine Type: 4-Stroke SOHC 4 Cylinder/16 Valves

Propshaft Horsepower: 100 HP @ 5,900 RPM

Weight: 359 lb. (163 kg)

Bore X Stroke: 3.0 in. x 3.5 in. (73 mm x 89.4 mm)



#### **BF115 - 20 in.**

Engine Type: 4-Stroke DOHC 4 cylinder/16 Valves

Propshaft Horsepower: 115 HP @ 5250 RPM

Weight: 478 lb. (217 kg)

Bore X Stroke: 3.43 in. x 3.9 in. (87 x 99 mm)





#### **BF115 - 25 in.**

Engine Type: 4-Stroke DOHC 4 cylinder/16 Valves

Propshaft Horsepower: 115 HP @ 5250 RPM

Weight: 485 lb. (220 kg)

Bore X Stroke: 3.43 in. x 3.9 in. (87 x 99 mm)



#### **BF135 - 20 in.**

Engine Type: 4-Stroke DOHC 4 Cylinder/16 Valves

Propshaft Horsepower: 135 HP @ 5,500 RPM

Weight: 478 lb. (217 kg)

Bore X Stroke: 3.4 in. x 3.9 in. (87 mm x 99 mm)



#### **BF135 - 25 in.**

Engine Type: 4-Stroke DOHC 4 Cylinder/16 Valves

Propshaft Horsepower: 135 HP @ 5,500 RPM

Weight: 485 lb. (220 kg)

Bore X Stroke: 3.4 in. x 3.9 in. (87 mm x 99 mm)



#### **BF150 - 20 in.**

Engine Type: 4-Stroke DOHC 4 Cylinder/16 Valves

Propshaft Horsepower: 150 HP @ 5,500 RPM

Weight: 478 lb. (217 kg)

Bore X Stroke: 3.4 in. x 3.9 in. (87 mm x 99 mm)



#### **BF150 - 25 in.**

Engine Type: 4-Stroke DOHC 4 Cylinder/16 Valves

Propshaft Horsepower: 150 HP @ 5,500 RPM

Weight: 485 lb. (220 kg)

Bore X Stroke: 3.4 in. x 3.9 in. (87 mm x 99 mm)





#### **BF200 - 20 in.**

Engine Type: 4-Stroke, SOHC, 60 deg. V6, 24 Valve

Propshaft Horsepower: 200 HP @ 5,500 RPM

Weight: 609 lb. (276 kg)

Bore X Stroke: 3.5 in. x 3.8 in. (89 mm x 96 mm)



#### **BF200 - 25 in.**

Engine Type: 4-Stroke, SOHC, 60 deg. V6, 24 Valve

Propshaft Horsepower: 200 HP @ 5,500 RPM

Weight: 622 lb. (282 kg)

Bore X Stroke: 3.5 in. x 3.8 in. (89 mm x 96 mm)



#### **BF225 - 20 in.**

Engine Type: 4-Stroke, SOHC, 60 deg. V6, 24 Valve

Propshaft Horsepower: 225 HP @ 5,500 RPM

Weight: 609 lb. (276 kg)

Bore X Stroke: 3.5 in. x 3.7 in. (89 mm x 93 mm)



#### **BF225 - 25 in.**

Engine Type: 4-Stroke, SOHC, 60 deg. V6, 24 Valve

Propshaft Horsepower: 225 HP @ 5,500 RPM

Weight: 622 lb. (282 kg)

Bore X Stroke: 3.5 in. x 3.8 in. (89 mm x 96 mm)



#### **BF225 - 30 in.**

Engine Type: 4-Stroke, SOHC, 60 deg. V6, 24 Valve

Propshaft Horsepower: 225 HP @ 5,500 RPM

Weight: 632 lb. (286 kg)

Bore X Stroke: 3.5 in. x 3.8 in. (89 mm x 96 mm)





#### **BF250 - 20 in.**

Engine Type: 4-Stroke, SOHC, 60 deg. V6, 24 Valve

Propshaft Horsepower: 250 HP @ 5800 RPM

Weight: 609 lb. (276 kg)

Bore X Stroke: 3.5 in. x 3.8 in. (89 in. x 96 mm)



#### **BF250 - 25 in.**

Engine Type: 4-Stroke, SOHC, 60 deg. V6, 24 Valve

Propshaft Horsepower: 250 HP @ 5800 RPM

Weight: 622 lb. (282 kg)

Bore X Stroke: 3.5 in. x 3.8 in. (89 x 96 mm)



#### **BF250 - 30 in.**

Engine Type: 4-Stroke, SOHC, 60 deg. V6, 24 Valve

Propshaft Horsepower: 250 HP @ 5800 RPM

Weight: 632 lb. (286 kg)

Bore X Stroke: 3.5 in. x 3.8 in. (89 x 96 mm)



#### **BFP260 - 20 in.**

Engine Type: 4-Stroke SOHC 3 Cylinder/12 Valves

Propshaft Horsepower: 60 HP @ 5,500 RPM

Weight: 256 lb. (116 kg)

Bore X Stroke: 2.9 in. x 3.1 in. (73 mm x 79.5 mm)



#### **BFP60 - 25 in.**

Engine Type: 4-Stroke SOHC 3 Cylinder/12 Valves

Propshaft Horsepower: 60 HP @ 5,500 RPM

Weight: 270 lb. (123 kg)

Bore X Stroke: 2.9 in. x 3.1 in. (73 mm x 79.5 mm)

